





Description

MGT is an united gas detector measuring four(4) major gases, which cause the most of the industrial accidents, to protect workers from the disasters caused by the Oxygen deficiency, Toxic gas poisoning and gas explosion. It measures continuously four(4) gases (O², CO, H²S and Combustible Gas(CH⁴)) and displays their concentrations and raises an alarm(visual, vibrating, and audible) when the risk occurs. It features the dual sensor of CO and H²S.

Key Feature

- Small size & Light weight
- Rechargeable battery
- 30EA of Bump tests/ Events/ Cal.
- Simultaneously detect 4 different gases
- 25 hours use by one charge for 4-6 hours (P-type)
- 60 days use by one charge for 4-6 hours (N-type)
- · Configuration via exclusive IR Link
- Easy check & calibration via Docking Station
- Intrinsic Safety

Specification

| Model | MGT | | |
|-------------------------|--|--|--|
| Self-test | Full function self-test upon activation | | |
| Jeli-lest | Sensors, battery and circuitry - continuous | | |
| Detecting Method | Diffusion | | |
| Display | LCD Display (back-light) | | |
| Alarm | LED flashing, Sound, Vibration | | |
| Sensor | O2, CO and H2S: Electrochemical Combustible(LEL): IR or Pellistor | | |
| IP | 67 | | |
| Temperature | -20°C ~ +50°C | | |
| Humidity | 5~95% RH(Non-condensing) | | |
| Battery | Rechargeable Li-ion power supply unit (2000mAh) | | |
| Charge Time | 4-6 hours | | |
| Battery Life | IR: 60 days continuous / Pellistor: 25 hours continuous | | |
| Low Battery Alarm | 20 minutes / 10 minutes / 5 minutes expired: 5 long beeps/flashes and then Off is displayed | | |
| Warranty | 2 years | | |
| Weight | 240g | | |
| Size | $61(w) \times 114(h) \times 43(d)$ mm | | |
| Optional Accessary | MGT-IR Link, Docking Station, SP-Pump 101 | | |
| | ATEX II 1 G Ex ia IIC T4 Ga | | |
| Approval | CSA Class 1, Zone 0, ex ia IIC T4 Ga | | |
| | IECEx Ex ia IIC T4 Ga | | |

Accessories

IR-Link

User can change alarm set points and upload firmware updates and download event logs and perform calibration.



Vehicle power adaptor



7CH Multi adaptor



Sampling pump (SP-Pump101)



Extension Probe 5M/ 10M



Multi Cradle



MGT Docking Station



Sensor specification

| GAS | Measuring range | Low Alarm | High Alarm |
|-----|-----------------|-----------|------------|
| 02 | 0~30%Vol | 19%Vol | 23%Vol |
| со | 0~500ppm | 30ppm | 60ppm |
| H2S | 0~100ppm | 10ppm | 30ppm |
| CH4 | 0~100%LEL | 10%LEL | 30%LEL |